



```

EXAMPLE OSCAM SERVER CONFIGURATION
2 CARDS: CAID1 AND CAID2

oscam.conf
-----
# MISC
[global]
logfile=/tmp/oscam.log
nice=-1
maxlogsize=0

# WEBINTERFACE OF PROXY OSCAM
[webif]
httpport=16002
httpuser=webifoscamproxy
httppwd=webifoscamproxy
httpallowed=127.0.0.1

# COMMUNICATION BETWEEN EYETVCAMD AND OSCAM SERVER
[newcamd]
port = 12006@CAID1:000000;12007@CAID2:000000
key = 0102030405060708091011121314

oscam.server
-----
# READERS FOR CAID1 AND CAID2
[reader]
device =
caid =
ident =
detect =
mhz =
cardmhz =

oscam.user
-----
# OSCAM PROXY USERS
[account]
user = user1
pwd = password1
group = 1,2
au = 1
caid = CAID1, CAID2
  
```

```

EXAMPLE EYETVCAMD CONFIGURATION
2 CARDS: CAID1 AND CAID2

EYETVCAMD ENTRY FOR CAID1:
-----
Protocol: ncd525
User: user1
Password: password1
Host: 192.168.178.1
Port: 12006
Key: 0102030405060708091011121314

EYETVCAMD ENTRY FOR CAID2:
-----
Protocol: ncd525
User: user1
Password: password1
Host: 192.168.178.1
Port: 12007
Key: 0102030405060708091011121314
  
```